


WING D LED

Unique Design Recessed
LED Luminaire with
Microprismatic or Opal Diffuser



CE **EAC**



Type: A unique recessed LED luminaire with microprismatic or opal diffuser for most commercial lighting applications.

Specification: Microprismatic (MPRZ LT92) or opal (OP LT80) diffuser.
Fully enclosed white steel body.
Luminaire is plastic wrapped and boxed individually.

Installation: Fits 15-24mm exposed T-Bar ceiling 600x600mm. When the luminaire is fitted into a plasterboard ceiling, it is recommended to use recessed mounting kit S620x620 (to be ordered separately).

Application: Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Life-time	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Wing D LED2x1700 D079 T840 MPRZ LT92	595x595x96	50000	3243	29	80+	4000	3,50
Wing D LED2x2400 D080 T840 MPRZ LT92	595x595x96	50000	4635	39	80+	4000	3,50
Wing D LED2x1700 D079 T840 OP LT80	595x595x96	50000	2959	29	80+	4000	3,50
Wing D LED2x2400 D080 T840 OP LT80	595x595x96	50000	4230	39	80+	4000	3,50

* Tolerance range for optical and electrical data: $\pm 10\%$

Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- TW – Tunable white
- BLT – Bluetooth unit (for wireless control via mobile device)
- EMG – Emergency version 1 hour
- EM3 – Emergency version 3 hours
- OP LT80 – Opal diffuser with 80% light transmission
- MPRZ LT92 – Microprismatic diffuser for a better glare protection
- WIE – 3-pole Wieland or similar connector
- W625 – To fit 625x625 suspended ceiling (subject to minimum quantity)
- RAL – RAL colours
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K

WING D LED2X1700 D079 T840 MPRZ LT92

