

CORONA S LED

Recessed LED Luminaire with Opal Diffuser



Type: A recessed mounted LED luminaire with opal diffuser for most commercial lighting applications.

Specification: Diffuser: high transmission opal (OP LT80).
Fully enclosed white steel body.
Luminaire is plastic-wrapped and boxed individually.

Installation: Fits 15-24mm exposed T-Bar ceiling 600x600mm.

Application: Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Corona S LED1x3800 D076 T840 OP LT80	595x595x75	50000	3758	33	80+	4000	3,00
Corona S LED1x4400 D077 T840 OP LT80	595x595x75	50000	4341	40	80+	4000	3,00
Corona S LED1x6000 D078 T840 OP LT80	595x595x75	50000	5994	60	80+	4000	3,00

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- BLT – Bluetooth unit (for wireless control via mobile device)
- EMG – Emergency version 1 hour
- EM3 – Emergency version 3 hours
- OP LT80 – Opal diffuser with 80% light transmission
- W625 – To fit 625x625 suspended ceiling (subject to minimum quantity)
- IP44 – IP44 protection degree
- RAL – RAL Colours
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K

CORONA S LED1X4400 D077 T840 OP LT80

