

CALIMA D LED

**New Concept Surface LED
Luminaire with
Microprismatic or
Opal Diffuser**



CEAC



CALIMA D LED1X3600 E284 T840 MPRZ LT92

Type: A new concept of surface mounted LED luminaires with microprismatic or opal diffuser for the majority of commercial lighting applications.

Specification: Diffuser: microprismatic (MPRZ LT92) or opal (OP LT80).
Body and gear tray: steel sheet painted in white. Body retaining clips for quick and easy installation. Luminaire is plastic-wrapped and boxed individually.

Installation: Surface luminaire is designed to be fixed to ceiling of any type or suspended.

Application: Indoor. Office buildings, shops, conference and educational environments.

Name	Overall dimensions (LxWxH), mm	Life-time	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Calima D LED1x1300 E275 T840 MPRZ LT92	595x295x60	50000	1213	11	80+	4000	2,00
Calima D LED1x1800 E276 T840 MPRZ LT92	595x295x60	50000	1703	15	80+	4000	2,00
Calima D LED1x2500 E278 T840 MPRZ LT92	595x295x60	50000	2433	21	80+	4000	2,00
Calima D LED2x1300 E279 T840 MPRZ LT92	595x595x60	50000	2426	21	80+	4000	3,00
Calima D LED2x1800 E280 T840 MPRZ LT92	595x595x60	50000	3405	29	80+	4000	3,00
Calima D LED2x2500 E282 T840 MPRZ LT92	595x595x60	50000	4867	39	80+	4000	3,00
Calima D LED3x1300 D302 T840 MPRZ LT92	595x595x60	50000	3639	29	80+	4000	3,00
Calima D LED3x1800 D303 T840 MPRZ LT92	595x595x60	50000	5108	43	80+	4000	3,00
Calima D LED3x2500 D304 T840 MPRZ LT92	595x595x60	50000	7300	59	80+	4000	3,00
Calima D LED1x2600 E283 T840 MPRZ LT92	1195x295x60	50000	2560	22	80+	4000	3,00
Calima D LED1x3600 E284 T840 MPRZ LT92	1195x295x60	50000	3594	30	80+	4000	3,00
Calima D LED1x5200 E286 T840 MPRZ LT92	1195x295x60	50000	5138	41	80+	4000	3,00
Calima D LED2x2600 E287 T840 MPRZ LT92	1195x595x60	50000	5121	41	80+	4000	6,00
Calima D LED2x3600 E288 T840 MPRZ LT92	1195x595x60	50000	7189	61	80+	4000	6,00
Calima D LED2x5200 E290 T840 MPRZ LT92	1195x595x60	50000	10277	83	80+	4000	6,00
Calima D LED1x3300 E291 T840 MPRZ LT92	1495x295x60	50000	3234	28	80+	4000	4,50

Name	Overall dimensions (LxWxH), mm	Life-time	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Calima D LED1x4600 E292 T840 MPRZ LT92	1495x295x60	50000	4540	38	80+	4000	4,50
Calima D LED1x6500 E294 T840 MPRZ LT92	1495x295x60	50000	6491	52	80+	4000	4,50

* Tolerance range for optical and electrical data: $\pm 10\%$


Name	Overall dimensions (LxWxH), mm	Life-time	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Calima D LED1x1300 E275 T840 OP LT80	595x295x60	50000	1112	11	80+	4000	2,00
Calima D LED1x1800 E276 T840 OP LT80	595x295x60	50000	1561	15	80+	4000	2,00
Calima D LED1x2500 E278 T840 OP LT80	595x295x60	50000	2231	21	80+	4000	2,00
Calima D LED2x1300 E279 T840 OP LT80	595x595x60	50000	2224	21	80+	4000	3,00
Calima D LED2x1800 E280 T840 OP LT80	595x595x60	50000	3122	29	80+	4000	3,00
Calima D LED2x2500 E282 T840 OP LT80	595x595x60	50000	4461	39	80+	4000	3,00
Calima D LED3x1300 D302 T840 OP LT80	595x595x60	50000	3336	29	80+	4000	3,00
Calima D LED3x1800 D303 T840 OP LT80	595x595x60	50000	4682	43	80+	4000	3,00
Calima D LED3x2500 D304 T840 OP LT80	595x595x60	50000	6692	59	80+	4000	3,00
Calima D LED1x2600 E283 T840 OP LT80	1195x295x60	50000	2347	22	80+	4000	3,00
Calima D LED1x3600 E284 T840 OP LT80	1195x295x60	50000	3295	30	80+	4000	3,00
Calima D LED1x5200 E286 T840 OP LT80	1195x295x60	50000	4710	41	80+	4000	3,00
Calima D LED2x2600 E287 T840 OP LT80	1195x595x60	50000	4694	41	80+	4000	6,00
Calima D LED2x3600 E288 T840 OP LT80	1195x595x60	50000	6590	61	80+	4000	6,00
Calima D LED2x5200 E290 T840 OP LT80	1195x595x60	50000	9420	83	80+	4000	6,00
Calima D LED1x3300 E291 T840 OP LT80	1495x295x60	50000	2965	28	80+	4000	4,50
Calima D LED1x4600 E292 T840 OP LT80	1495x295x60	50000	4162	38	80+	4000	4,50
Calima D LED1x6500 E294 T840 OP LT80	1495x295x60	50000	5950	52	80+	4000	4,50

* Tolerance range for optical and electrical data: $\pm 10\%$

Options available on request:

- | | | | |
|------|--|-----------|---|
| DALI | - DALI driver | OP LT80 | - Opal diffuser with 80% light transmission |
| SDIM | - Switch-control/dimming | MPRZ LT92 | - Microprismatic diffuser for a better glare protection |
| TW | - Tunable white | | |
| BLT | - Bluetooth unit (for wireless control via mobile device) | IP44 | - IP44 protection degree |
| EMG | - Emergency version 1 hour | RAL | - RAL colours |
| EM3 | - Emergency version 3 hours | T830 | - Colour temperature 3000K |
| 5TB | - 5 way terminal block with two holes (for in and out going cable) | T840 | - Colour temperature 4000K |

CALIMA D LED2X1800 E280 T840 MPRZ LT92



CALIMA D LED2X1800 E280 T840 OP LT80

