

MARENCO

T5 & T8 Surface Luminaire with Prismatic Diffuser



Type: Economical surface mounted T8 luminaire with a modern low profile body and prismatic diffuser.

Specification: UV stable prismatic diffuser is fitted to the body with a steel frame.
Fully enclosed painted steel body.
Luminaire is plastic-wrapped and packed in twin boxes.

Installation: Surface luminaire designed to be fixed to ceiling of any type.

Application: Indoor. Office buildings, shops, sport halls and other commercial environments.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Marenco 118 J98	1x18 (G13)	635x220x66	1,8	22
Marenco 218 J99	2x18 (G13)	635x220x66	2,2	42
Marenco 218 H76	2x18 (G13)	635x360x66	2,4	42
Marenco 318 L28	3x18 (G13)	635x360x66	2,8	64
Marenco 318 L29	3x18 (G13)	635x635x66	4	64
Marenco 418 D10	4x18 (G13)	635x635x66	4,2	84
Marenco 136 L01	1x36 (G13)	1245x220x66	3,2	42
Marenco 236 L02	2x36 (G13)	1245x220x66	3,8	84
Marenco 236 L30	2x36 (G13)	1245x360x66	4	84
Marenco 336 L04	3x36 (G13)	1245x360x66	4,6	126

Options available on request:

HF	– High Frequency control gear	EMG	– Emergency version 1 hour
DIM	– Dimmable ballast	EM3	– Emergency version 3 hours
SDIM	– Switch-control/dimming	5TB	– 5 way terminal block for loop feed and ease of wiring
DALI	– DALI ballast	NCP	– Low Power Factor