

LEVANTO & MARENCO LED

Surface Luminaire with Opal or Prismatic Diffuser



LEVANTO S LED2X2350 B145
T840



LEVANTO S LED2X2350 B145 T840
SPORT

Type: Economical surface mounted LED luminaire with a modern low profile body and diffuser.

Specification: UV stable opal (Levanto) or prismatic (Marenco) sheet is fitted to the body with a steel frame. Option SPORT is equipped with a special white painted steel protective grid for sport halls and others areas, where a high degree of protection is required.
Fully enclosed painted steel body.
Luminaire is plastic-wrapped and packaged in twin boxes.

Installation: Surface luminaire designed to be fixed to ceilings of any type.

Application: Office buildings, shops, sport halls and other commercial environments.

Options available on request:

DIM – Dimmable ballast 1-10V
 SWITCHDIM – Switch DIM ballast
 DALI – DALI ballasts
 EMG – Emergency version 1 hour
 EM2 – Emergency version 2 hours
 EM3 – Emergency version 3 hours

MPRZ – Mikroprismatic diffuser
 T830 – Color temperature 3000K
 T840 – Color temperature 4000K
 T857 – Color temperature 5700K
 SPORT – White painted steel protective grid
 L80 – Opal sheet with 80% light transmission

Type	Overall dimensions, mm	Luminous flux, lm	Color temperature, K	Color rendering, Ra	Total wattage, W	Weight, kg
Levanto S LED2x1050 B142 T840	360x635x66	2100	4000	>80	16	2
Levanto S LED2x1400 B574 T840	360x635x66	2800	4000	>80	23	2
Levanto S LED2x2000 B575 T840	360x635x66	4000	4000	>80	33	2
Levanto S LED3x1050 B143 T840	635x635x66	3150	4000	>80	24	3
Levanto S LED3x1400 B576 T840	635x635x66	4200	4000	>80	35	3
Levanto S LED3x2000 B577 T840	635x635x66	6000	4000	>80	50	3
Levanto S LED4x1050 B144 T840	635x635x66	4200	4000	>80	31	3
Levanto S LED4x1400 B578 T840	635x635x66	5600	4000	>80	46	3
Levanto S LED4x2000 B579 T840	635x635x66	8000	4000	>80	66	3
Levanto S LED1x2350 B580 T840	220x1245x66	2350	4000	>80	17	3
Levanto S LED1x3150 B581 T840	220x1245x66	3150	4000	>80	25	3
Levanto S LED1x4300 B582 T840	220x1245x66	4300	4000	>80	36	3
Levanto S LED2x2350 B145 T840	220x1245x66	4700	4000	>80	34	3
Levanto S LED2x3150 B583 T840	220x1245x66	6300	4000	>80	49	3
Levanto S LED2x4300 B584 T840	220x1245x66	8600	4000	>80	71	3
Levanto S LED2x2350 B146 T840	360x1245x66	4700	4000	>80	34	3,5
Levanto S LED2x3150 B585 T840	360x1245x66	6300	4000	>80	49	3,5
Levanto S LED2x4300 B586 T840	360x1245x66	8600	4000	>80	71	3,5
Levanto S LED3x2350 B147 T840	635x1245x66	7050	4000	>80	50	3,5
Levanto S LED3x3150 B587 T840	635x1245x66	9450	4000	>80	74	3,5
Levanto S LED3x4300 B588 T840	635x1245x66	12900	4000	>80	107	3,5
Marengo S LED2x1050 B148 T840	360x635x66	2100	4000	>80	16	2
Marengo S LED2x1400 B589 T840	360x635x66	2800	4000	>80	23	2
Marengo S LED2x2000 B590 T840	360x635x66	4000	4000	>80	33	2
Marengo S LED3x1050 B149 T840	635x635x66	3150	4000	>80	24	3
Marengo S LED3x1400 B591 T840	635x635x66	4200	4000	>80	35	3
Marengo S LED3x2000 B592 T840	635x635x66	6000	4000	>80	50	3
Marengo S LED4x1050 B150 T840	635x635x66	4200	4000	>80	31	3
Marengo S LED4x1400 B593 T840	635x635x66	5600	4000	>80	46	3
Marengo S LED4x2000 B594 T840	635x635x66	8000	4000	>80	66	3
Marengo S LED1x2350 B595 T840	220x1245x66	2350	4000	>80	17	3
Marengo S LED1x3150 B596 T840	220x1245x66	3150	4000	>80	25	3
Marengo S LED1x4300 B597 T840	220x1245x66	4300	4000	>80	36	3
Marengo S LED2x2350 B151 T840	220x1245x66	4700	4000	>80	34	3
Marengo S LED2x3150 B598 T840	220x1245x66	6300	4000	>80	49	3
Marengo S LED2x4300 B599 T840	220x1245x66	8600	4000	>80	71	3
Marengo S LED2x2350 B152 T840	360x1245x66	4700	4000	>80	34	3,5
Marengo S LED2x3150 B600 T840	360x1245x66	6300	4000	>80	49	3,5
Marengo S LED2x4300 B601 T840	360x1245x66	8600	4000	>80	71	3,5
Marengo S LED3x2350 B153 T840	635x1245x66	7050	4000	>80	50	3,5
Marengo S LED3x3150 B602 T840	635x1245x66	9450	4000	>80	74	3,5
Marengo S LED3x4300 B603 T840	635x1245x66	12900	4000	>80	107	3,5

MARENGO S LED4X1050 B150 T840

