



Sirocco 218 A29

| Туре: | A premium surface mounted T8 luminaire with a modern low profile body. | | |
|----------------|---|--|--|
| Specification: | Double Parabolic louvre, with perforated inserts to give better light distribution. Louvre is fitted into the body with a locking safety clip for maximum stability. Nylon retainers enable louvre to swing down for maintenance and tube replacement. Fully enclosed white steel body, wiring is concealed and not visible from ground level. Luminaire is plastic-wrapped and packaged in twin boxes. | | |
| Installation: | Surface luminaire designed to be fixed to ceilings of any type. | | |
| Application: | Office buildings, shops and other commercial environments. | | |

| Туре | Lamp (W) and holder | Overall dimensions, mm | Weight, kg | Total wattage, W |
|-----------------|---------------------|------------------------|------------|------------------|
| Sirocco 218 A29 | 2×18 (G13) | 360×635×66 | 2,4 | 50 |
| Sirocco 418 A28 | 4×18 (G13) | 635×635×66 | 3,8 | 84 |

Options available on request:

| HF | _ | High Frequency control gear | EM2 | _ | Emergency version 2 hours |
|-----------|---|-----------------------------|-----|---|---|
| DIM | - | Dimmable ballast 1-10V | EM3 | _ | Emergency version 3 hours |
| SWITCHDIM | - | Switch DIM ballast | 4TB | _ | 4 way terminal block for loop feed and ease of wiring |
| DALI | - | DALI ballast | MAT | _ | Matt reflector |
| EMG | - | Emergency version 1 hour | NCP | _ | Low Power Factor |