

Recessed Downlight for Compact Fluorescent Lamp with Frosted Glass Cover



Application: Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Lamp (W) and holder	Overall dimensions (cut-out), mm	Weight, kg	Total wattage, W
Orion 113 D45 OP	1x13W (G24d-1)	ø193(165)x100	1,3	19
Orion 213 D46 OP	2x13W (G24d-1)	ø193(165)x100	1,7	38
Orion 118 E60 OP	1x18W (G24d-2)	ø193(165)x100	1,4	26
Orion 218 B27 OP	2x18W (G24d-2)	ø193(165)x100	1,8	52
Orion 126 I95 OP	1x26W (G24d-3)	ø193(165)x100	1,5	34
Orion 226 I96 OP	2x26W (G24d-3)	ø193(165)x100	1,9	68
Orion 126 D47 OP	1x26W (G24d-3)	ø235(210)x126	1,6	34
Orion 226 B28 OP	2x26W (G24d-3)	ø235(210)x126	2,1	68

HF	-	High Frequency control gear
DIM	-	Dimmable ballast
SDIM	-	Switch-control/dimming
DALI	-	DALI ballast
EMG	-	Emergency version 1 hour
EM3	-	Emergency version 3 hours
5TB	-	5 way terminal block for loop feed and ease of wiring
PRZ	-	Prismatic diffuser
CLR	-	Clear glass
IP44	-	IP44 protection degree
RAL	-	RAL colours