

ORION SOP

Recessed Downlight for
Compact Fluorescent Lamps
with Frosted Glass Cover



Orion 226 B28 SOP CLR



Orion 226 B28 SOP PRZ

Type: Recessed downlight with frosted glass cover for compact fluorescent lamps.

Specification: Aluminium reflector with white powder coated steel ring. Frosted glass cover. Body in steel in white finish, gearbox in grey finish. Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for plasterboard or similar types of ceiling, requires a cut-out.

Application: Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Lamp (W) and holder	Overall dimensions (cut-out), mm	Weight, kg	Total wattage, W
Orion 113 D45 SOP	1x13W (G24d-1)	ø193(165)x100	1,3	19
Orion 213 D46 SOP	2x13W (G24d-1)	ø193(165)x100	1,7	38
Orion 118 E60 SOP	1x18W (G24d-2)	ø193(165)x100	1,4	26
Orion 218 B27 SOP	2x18W (G24d-2)	ø193(165)x100	1,8	52
Orion 126 I95 SOP	1x26W (G24d-3)	ø193(165)x100	1,5	34
Orion 226 I96 SOP	2x26W (G24d-3)	ø193(165)x100	1,9	68
Orion 126 D47 SOP	1x26W (G24d-3)	ø235(210)x126	1,6	34
Orion 226 B28 SOP	2x26W (G24d-3)	ø235(210)x126	2,1	68
Orion 132 J40 SOP HF	1x32W (Gx24q-3)	ø235(210)x126	1,2	32
Orion 142 J41 SOP HF	1x42W (Gx24q-4)	ø235(210)x126	1,2	44
Orion 132 J38 SOP HF	1x32W (Gx24q-3)	ø265(235)x178	1,7	32
Orion 232 K28 SOP HF	2x32W (Gx24q-3)	ø265(235)x178	1,8	64
Orion 142 J39 SOP HF	1x42W (Gx24q-4)	ø265(235)x178	1,7	44

Options available on request:

- HF – High Frequency control gear
- DIM – Dimmable ballast
- SDIM – Switch-control/dimming
- DALI – DALI ballast
- EMG – Emergency version 1 hour
- EM3 – Emergency version 3 hours
- 5TB – 5 way terminal block for loop feed and ease of wiring
- RAL – RAL colours
- CLR – Clear glass
- MPRZ – Microprismatic diffuser
- PRZ – Prismatic diffuser

ORION 218 B27 SOP HF

