

# CORONA C LED

## Recessed LED Luminaire with Circular Diffuser



**Type:** A recessed mounted LED luminaire with circular opal diffuser for most commercial lighting applications.

**Specification:** Diffuser: high transmission opal (OP LT80).  
Fully enclosed white steel body.  
Luminaire is plastic-wrapped and boxed individually.

**Installation:** Fits 15-24mm exposed T-Bar ceiling 600x600mm.

**Application:** Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Life-time	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Corona C LED1x3100 D067 T840 OP LT80	595x595x70	50000	3006	29	80+	4000	3,10
Corona C LED1x4300 D068 T840 OP LT80	595x595x70	50000	4227	39	80+	4000	3,10
Corona C LED1x5900 D069 T840 OP LT80	595x595x70	50000	5859	57	80+	4000	3,10

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- TW – Tunable white
- BLT – Bluetooth unit (for wireless control via mobile device)
- EMG – Emergency version 1 hour
- EM3 – Emergency version 3 hours
- OP LT80 – Opal diffuser with 80% light transmission
- W625 – To fit 625x625 suspended ceiling (subject to minimum quantity)
- IP44 – IP44 protection degree
- RAL – RAL colours
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K

### CORONA C LED1X4300 D068 T840 OP LT80

