

BREEZE DPA

T5 & T8 Recessed Luminaire
with Double Parabolic Louvre



BREEZE 414 M70

Type:	A recessed T5/T8 luminaire with a double parabolic louvre.
Specification:	A glossy double parabolic reflector with glossy cross blades. Louvre is fitted into the body with locking safety clips for maximum stability. Fully enclosed painted steel body, wiring is concealed and not visible from ground level. Luminaire is plastic-wrapped and packed in twin boxes.
Installation:	Fits 15-24mm exposed T-Bar ceiling 600x600mm. When the luminaire is fitted into a plasterboard ceiling, it is recommended to use recessed mounting kit S620x620 (to be ordered separately).
Application:	Indoor. Office buildings, shops and other commercial environments.

Type	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Breeze 418 I92	4x18 (G13)	595x595x72	3,7	84
Breeze 414 M70	4x14 (G5)	595x595x72	2,9	62
Breeze 424 M71	4x24 (G5)	595x595x72	2,9	98

2 or 3 Tube (2/3x18/14W) versions are available on request

Options available on request:

HF	– High Frequency control gear	5TB	– 5 way terminal block for loop feed and ease of wiring
DIM	– Dimmable ballast 1-10V	MAT	– Matted reflector (subject to minimum quantity)
SDIM	– Switch-control/dimming	WIE	– 3-pole Wieland or similar connector (subject to minimum quantity)
DALI	– DALI ballast		
EMG	– Emergency version 1 hour	QCK	– Quick connection version, includes tubes.
EM3	– Emergency version 3 hours		