

# LYRA R LED

## Decorative LED Luminaire



CE EAC



**Type:** A decorative and modern LED luminaire in four sizes to fit wide range of applications.

**Specification:** Opal acrylic diffuser.  
White powder coated body and recessed mounting frame with quick lock system.  
Luminaire is plastic-wrapped and boxed individually.

**Installation:** Suitable for plasterboard or similar type of ceiling, requires a cut-out.

**Application:** Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Lyra R LED1x1800 D083 T840 OP LT80	Ø320x180	50000	1798	19	80+	4000	4,00
Lyra R LED1x2600 D084 T840 OP LT80	Ø320x180	50000	2526	27	80+	4000	4,00
Lyra R LED1x3300 D085 T840 OP LT80	Ø470x180	50000	3251	31	80+	4000	6,80
Lyra R LED1x4500 D086 T840 OP LT80	Ø470x180	50000	4493	44	80+	4000	6,80
Lyra R LED1x5900 D087 T840 OP LT80	Ø620x190	50000	5849	55	80+	4000	10,00
Lyra R LED1x7000 D088 T840 OP LT80	Ø620x190	50000	6985	67	80+	4000	10,00
Lyra R LED1x8400 D089 T840 OP LT80	Ø920x210	50000	8332	80	80+	4000	14,00
Lyra R LED1x10200 D090 T840 OP LT80	Ø920x210	50000	10116	100	80+	4000	14,00

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- TW – Tunable white
- BLT – Bluetooth unit (for wireless control via mobile device)
- EMG – Emergency version 1 hour
- EM3 – Emergency version 3 hours
- OP LT80 – Opal diffuser with 80% light transmission
- 5TB – 5 way terminal block with two holes (for in and out going cable)
- RAL – RAL colours
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K

### LYRA R LED1X4500 D086 T840 OP LT80

