


ALCOR DELUXE

**Double T5 Batten Luminaire
with Adjustable Arm**



Type:	Double T5 batten luminaire with adjustable arm for mounting on MECA type profiles.
Specification:	Specular aluminum reflector. Body and adjustable arms in white steel. Luminaire body is plastic-wrapped and boxed individually. Reflectors are packaged separately (16 pcs per box).
Installation:	Designed to be mounted on MECA type profiles.
Application:	Warehouses, factories, supermarkets, other commercial environments.

Type	Lamp (W) and holder	Overall dimensions, mm	Weight, kg	Total wattage, W
Alcor 2x228 K18 Deluxe	2x2x28 (G5)	146x3000-2450x76	5,8	120
Alcor 2x254 K19 Deluxe	2x2x54 (G5)	146x3000-2450x76	5,8	232
Alcor 2x235 K20 Deluxe	2x2x35 (G5)	146x3600-3050x76	6,8	150
Alcor 2x249 K21 Deluxe	2x2x49 (G5)	146x3600-3050x76	6,8	208

Options available on request:

DALI	- DALI ballast	*CBF3x1,5	- Outgoing flexcable 3x1,5mm ² ready for connection (*-length, m)
SWITCHDIM	- Switch DIM ballast	*CBF5x1,5	- Outgoing flexcable 5x1,5mm ² ready for connection (*-length, m)
DIM	- Dimmable ballast 1-10V	*CBF3x2,5	- Outgoing flexcable 3x2,5mm ² ready for connection (*-length, m)
EMG	- Emergency version 1 hour	*CBF5x2,5	- Outgoing flexcable 5x2,5mm ² ready for connection (*-length, m)
EM2	- Emergency version 2 hours	NAC31S.W	- ENSTO NET connector
EM3	- Emergency version 3 hours	NAC32S.W	- ENSTO NET connector
Deluxe	- Symmetrical aluminum reflector	NAC51S.W	- ENSTO NET connector
1LIN	- Through wiring 3x1.5 mm ² with two push-in terminals	NAC52S.W	- ENSTO NET connector
3LIN	- Through wiring 5x1.5 mm ² with two push-in terminals	**CON3/5	- 3 or 5 poles connector (**- male (M) and female (F) type)
1LIN2,5	- Through wiring 3x2.5 mm ² with two push-in terminals	5TB	- 5 way terminal block with two holes (for in and out going cable)
3LIN2,5	- Through wiring 5x2.5 mm ² with two push-in terminals		