

ANDROMEDA LED

Budget LED Downlight with Opal Diffuser



CE **EAC**



Type: A budget range of recessed LED downlights with opal diffuser for installations with minimum ceiling void.

Specification: Opal diffuser.
Body in aluminium in white finish. Tool free spring clip installation.
Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for plasterboard or similar types of ceiling, requires a cut-out.

Application: Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Andromeda LED1x800 B876 T840 OP	Ø125(100)x66	30000	800	10	80+	4000	0,15
Andromeda LED1x1040 B877 T840 OP	Ø150(125)x72	30000	1040	12	80+	4000	0,17
Andromeda LED1x1280 B878 T840 OP	Ø181(165)x82	30000	1280	16	80+	4000	0,22
Andromeda LED1x1680 B879 T840 OP	Ø227(210)x97	30000	1680	20	80+	4000	0,26

* Tolerance range for optical and electrical data: $\pm 10\%$

Options available on request:

- OP – Opal diffuser
- T840 – Colour temperature 4000K

ANDROMEDA LED1X1280 B878 T840 OP

