

ANTLIA C LED

Surface LED Downlight with Opal Diffuser



CE EAC



Type: Surface mounted LED downlight with opal diffuser.

Specification: Opal diffuser with white coated ring.
White painted aluminium body. IP44 ingress protection.
Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for surface mounting on ceiling.

Application: Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

| Name | Overall dimensions (LxWxH), mm | Lifetime | Luminaire output*, lm Ta=25°C | System power*, W | CRI (Ra) | CCT, K | Weight, kg |
|---------------------------------|--------------------------------|----------|-------------------------------|------------------|----------|--------|------------|
| Antlia C LED1x1400 D345 T840 OP | Ø200x130 | 50000 | 1321 | 12 | 80+ | 4000 | 1,00 |
| Antlia C LED1x1900 D346 T840 OP | Ø200x130 | 50000 | 1858 | 16 | 80+ | 4000 | 1,00 |
| Antlia C LED1x2600 D347 T840 OP | Ø200x130 | 50000 | 2575 | 23 | 80+ | 4000 | 1,00 |

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- OP – Opal diffuser
- MPRZ – Microprismatic diffuser
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K
- RAL – RAL colours

ANTLIA C LED1X1900 D346 T840 OP

